

NOTICE OF PROPOSED DEVELOPMENT

Notice is hereby given that an application has been made for planning approval for the following development:

SITE: 8 Spoonbill Loop, Sorell (CT187/106/30)

PROPOSED DEVELOPMENT:


DWELLING

The relevant plans and documents can be inspected at the Council Offices at 47 Cole Street, Sorell during normal office hours, or the plans may be viewed on Council's website at www.sorell.tas.gov.au until **Monday 5th August 2024.**

Any person may make representation in relation to the proposal by letter or electronic mail (<u>sorell.council@sorell.tas.gov.au</u>) addressed to the General Manager. Representations must be received no later than **Monday 5**th **August 2024.**

APPLICANT: Wilson Homes Pty Ltd

APPLICATION NO: DA 2024 / 72 - 1
DATE: 18 July 2024



18-Jul-2024

100 m

Disclaimer: This map is a representation of the information currently held by Sorell Council. While every effort has been made to ensure the accuracy of the product, Council accepts no responsibility for any errors or omissions. Any feedback on omissions or errors would be appreciated.

Part B: Please note that Part B of this form is publicly exhibited.

Full description of Proposal:	Use: New Building						
or roposur.	Development: Dwelling						
	Large or complex proposals s	should be	described	in a letter or planning report.			
Design and construction cost of proposal:			\$ 420,00	00			
Is all, or some th	e work already constructed:		No: 🏻	Yes: □			
Location of	Street address Lot 30 Spo	oonbill	LoopSu	burb: Sorell Postcode: 71	L72		
proposed works:	Certificate of Title(s) Volun	ne:		Folio:			
			SORELL	Sorell Council			
Current Use of Site	Vacant Land Development Application: Development Application -Lot 30 Spoonbill Loop, Sorell - P1.pdf						
			Date R	Reference:P1 Received:12/04/2024			
Current Owner/s:	Name(s) Jac Group						
		 		1			
Is the Property of Register?	on the Tasmanian Heritage	No: X□	Yes: □	If yes, please provide written ac from Heritage Tasmania	dvice		
Is the proposal t than one stage?	to be carried out in more	No: X□	Yes: □	If yes, please clearly describe in	plans		
Have any potentially contaminating uses been undertaken on the site?			Yes:	If yes, please complete the Additional Information for Non-Residential Use			
Is any vegetation proposed to be removed?			Yes:	If yes, please ensure plans clear area to be impacted	rly show		
Does the proposal involve land administered or owned by either the Crown or Council?			Yes:	If yes, please complete the Cou Crown land section on page 3	ncil or		
If a new or upgraded vehicular crossing is required from Council to the front boundary please							
complete the Vehicular Crossing (and Associated Works) application form							
https://www.soi	rell.tas.gov.au/services/engir	neering/					

Declarations and acknowledgements

- I/we confirm that the application does not contradict any easement, covenant or restriction specified in the Certificate of Title, Schedule of Easements or Part 5 Agreement for the land.
- I/we consent to Council employees or consultants entering the site and have arranged permission and/or access for Council's representatives to enter the land at any time during normal business hours.
- I/we authorise the provision of a copy of any documents relating to this application to any person for the purposes of assessment or public consultation and have permission of the copyright owner for such copies.
- I/we declare that, in accordance with s52(1) of the Land Use Planning and Approvals Act 1993, that I have notified the owner(s) of the intention to make this application.
- I/we declare that the information in this application is true and correct.

Details of how the Council manages personal information and how you can request access or corrections to it is outlined in Council's Privacy Policy available on the Council website.

- I/we acknowledge that the documentation submitted in support of my application will become a public record held by Council and may be reproduced by Council in both electronic and hard copy format in order to facilitate the assessment process, for display purposes during public exhibition, and to fulfil its statutory obligations. I further acknowledge that following determination of my application, Council will store documentation relating to my application in electronic format only.
- Where the General Manager's consent is also required under s.14 of the *Urban Drainage Act 2013*, by making this application I/we also apply for that consent.

Signature: Date:

Crown or General Manager Land Owner Consent

If the land that is the subject of this application is owned or administered by either the Crown or Sorell Council, the consent of the relevant Minister or the Council General Manager whichever is applicable, must be included here. This consent should be completed and signed by either the General Manager, the Minister, or a delegate (as specified in s52 (1D-1G) of the *Land Use Planning and Approvals Act 1993*).

Please note:

- If General Manager consent if required, please first complete the General Manager consent application form available on our website www.sorell.tas.gov.au
- If the application involves Crown land you will also need a letter of consent.
- Any consent is for the purposes of making this application only and is not consent to undertaken work or take any other action with respect to the proposed use or development.

I	being responsible for the
administration of land at	Soreil Councii
declare that I have given permission for the making of this application for	Development Application: Development Application -Lot 30 Spoonbill Loop, Sorell - P1.pdf
	Plans Reference:P1 Date Received:12/04/2024

Signature of General Manager, Minister or Delegate:

Signature:



Development Application: Development Application -Lot 30 Spoonbill Loop, Sorell - P1.pdf

AS2870:2011 SITE ASSESSMENT

Lot 30 Pittwater Shores Estate

Sorell

February 2024

Wilson Homes Reference: 713965/0200







GEO-ENVIRONMENTAL

SOLUTIONS



Development Application: Development Application -Lot 30 Spoonbill Loop, Sorell - P1.pdf

Plans Reference:P1 Date Received:12/04/2024

Disclaimer: The author does not warrant the information contained in this document is free from errors or omissions. The author shall not in any way be liable for any loss, damage or injury suffered by the User consequent upon, or incidental to, the existence of errors in the information.



Investigation Details

Client: Wilson Homes

Site Address: Lot 30 Pittwater Shores Estate, Sorell

Date of Inspection: 16/02/2024

Proposed Works: New house

Investigation Method: Geoprobe 540UD - Direct Push

Inspected by: M. Campbell

Site Details

Certificate of Title (CT): TBC

Title Area: Approx. 470 m²

Applicable Planning Overlays:

Priority Vegetation, Airport obstacle limitation area,

Waterway and Coastal Protection Areas

Slope & Aspect: Flat with no dominant aspect facing slope

Vegetation: Grass & Weeds Fill

Background Information

Geology Map: MRT

Geological Unit: Tertiary Basalt

Climate: Annual rainfall 550mm

Water Connection: Mains

Sewer Connection: Serviced-Mains

Testing and Classification: AS2870:2011, AS1726:2017 & AS4055:2021



Development Application: Development Application -Lot 30 Spoonbill Loop, Sorell - P1.pdf



Investigation

A number of bore holes were completed to identify the distribution and variation of the soil materials at the site, bore hole locations are indicated on the site plan. See soil profile conditions presented below. Tests were conducted across the site to obtain bearing capacities of the material at the time of this investigation.

Soil Profile Summary

BH 1 Depth (m)	BH 2 Depth (m)	USCS	Description	
0.00-0.10	0.00-0.20	CI	FILL: Silty CLAY : medium plasticity, dark grey, brown, slightly moist, stiff	
0.10-2.10	0.20-2.10	СН	Silty CLAY : high plasticity, dark grey, yellow, brown, slightly moist, firm to stiff,	
2.10-2.30	2.10-2.20	GC	Clayey GRAVEL: medium plasticity, yellow, dry very dense, refusal.	

Site Notes

Soils on the site are developing from Tertiary basalt, the clay fraction is likely to show significant ground surface movement with moisture fluctuations.

Site Classification

The site has been assessed and classified in accordance with AS2870:2011 "Residential Slabs and Footings".

The site has been classified as:

Class P

Y's range: **75-85mm**

Notes: due to low bearing capacity of the underlying soil





Wind Loading Classification

According to "AS4055:2021 - Wind Loads for Housing" the house site is classified below:

Wind Classification:	N3
Region:	Α
Terrain Category:	1.0
Shielding Classification:	NS
Topographic Classification:	T1
Wind Classification:	N3
Design Wind Gust Speed $-$ m/s ($V_{h,u}$):	50

Construction Notes & Recommendations

The site has been classified as Class P - see 'Site Classification' above.

All foundations must penetrate through any fill material & topsoil and into the residual soil/gravel below with bearing capacities >100kPa.

All earthworks on site must comply with AS3798:2012, and I further recommend that consideration be given to drainage and sediment control on site during and after construction. Care should also be taken to ensure there is adequate drainage in the construction area to avoid the potential for weak bearing and foundation settlement associated with excessive soil moisture.

I also recommend that during construction that I and/or the design engineer be notified of any major variation to the foundation conditions as predicted in this report.

Dr John Paul Cumming B.Agr.Sc (hons) PhD CPSS GAICD Director





Explanatory Notes

1 Scope of Works

The methods of description and classification of soils used in this report are based largely on Australian Standard 1726 – Geotechnical Site Investigations (AS1726:2017), with reference to Australian Standard 1289 – Methods for testing soils for engineering purposes (AS1289), for eventual Site Classification according to Australian Standard 2870 (AS2870:2011) – Residential Slabs and Footings and Australian Standard 1547 (AS1547:2012) On-site domestic wastewater management.

1.1 Site Classification AS2870:2011

Site classification with reference to the above Australian Standards are based on site reactivity.

Class	Foundation Conditions	Characteristic Surface Movement
Α	Most sand and rock sites with little or no ground movement from moisture changes.	0mm
S	Slightly reactive clay sites, which may experience only slight ground movement from moisture changes.	0 – 20mm
М	Moderately reactive clay or silt sites, which may experience moderate ground movement from moisture changes.	20 – 40mm
H-1	Highly reactive clay sites, which may experience high ground movement from moisture changes.	40 – 60mm
H-2	Highly reactive clay sites, which may experience very high ground movement from moisture changes.	60 – 75mm
Е	Extremely reactive sites, which may experience extreme ground movement from moisture changes.	>75mm

Note: Soils where foundation performance may be significantly affected by factors other than reactive soil movement are classified as **Class P**.

A site is classified as Class P when:

- The bearing capacity of the soil profile in the foundation zone is generally less than 100kpa
- If excessive foundation settlement may occur due to loading on the foundation.
- The site contains uncontrolled fill greater than 0.8m in depth for sandy sites and 0.4m in depth for other soil materials.
- The site is subject to mine subsistence, landslip, collapse activity or coastal erosion.
- The site is underlain by highly dispersive soils with significant potential for erosion
- If the site is subject to abnormal moisture conditions which can affect foundation performance







1.2 Soil Characterisation

This information explains the terms of phrase used within the soil description area of the report.

It includes terminology for cohesive and non-cohesive soils and includes information on how the Unified Soil Classification Scheme (USCS) codes are determined.

NON COHESIVE – SAND & GRAVEL						
Consistency Description	Field Test	Dynamic Cone Penetrometer blows/100 mm				
Very loose (VL)	Easily penetrated with 13 mm reinforcing rod pushed by hand.	0 - 1				
Loose (L)	Easily penetrated with 13 mm reinforcing rod pushed by hand. Can be excavated with a spade; 50 mm wooden peg can be easily driven.	1 - 3				
Medium dense (MD)	Penetrated 300 mm with 13 mm reinforcing rod driven with 2 kg hammer, - hard shovelling.	3 - 8				
Dense (D)	Penetrated 300 mm with 13 mm reinforcing rod driven with 2 kg hammer, requires pick for excavation: 50 mm wooden peg hard to drive.	8 - 15				
Very dense (VD)	Penetrated only 25 - 50 mm with 13 mm reinforcing rod driven with 2 kg hammer.	>15				

COHESIVE - SILT & CLAY						
Consistency Description	Field Test	Indicative undrained shear strength kPa				
Very soft	Easily penetrated >40 mm by thumb. Exudes between thumb and fingers when squeezed in hand.	<12				
Soft	Easily penetrated 10 mm by thumb. Moulded by light finger pressure	>12 and <25				
Firm	Impression by thumb with moderate effort. Moulded by strong finger pressure	>25 and <50				
Stiff	Slight impression by thumb cannot be moulded with finger.	>50 and <100				
Very Stiff	Very tough. Readily indented by thumbnail.	>100 and <200				
Hard	Brittle. Indented with difficulty by thumbnail.	>200				



Development Application: Development Application -Lot 30 Spoonbill Loop, Sorell - P1.pdf







1.3 USCS Material Descriptions

Soils for engineering purposes are the unconsolidated materials above bedrock, they can be residual, alluvial, colluvial or aeolian in origin.

Major Divisions		Particle size mm Symbol USCS Group Typical Names Symbol		Laboratory Classification						
(mu	BOULDERS	200			%<(0.075 mm (2)	Plasticity of fine fraction	$C_{ii} = \frac{D_{iii}}{D_{iii}}$	$C_{v} = \frac{(D_{so})^{2}}{(D_{so})(D_{so})}$	NOTES
	COBBLES									
Than 0.075 mm)		63	GW	Well graded gravels and gravel-sand mixtures, little or no fines		0-5	2 - 2	>4	Between 1 and 3	(1) Identify fines by the method given
Sarger	GRAVELS (more than	coarse 20	GP	Poorly graded gravels and gravel-sand mixtures, little or no fines, uniform gravels	given in 'Major Divisions'	0-5	3 73 9		comply with	for fine-grained
S €	half of coarse	medium	GM	Silty gravels, gravel-sand-silt mixtures (1)	'Major (12-50	Below 'A' line or PI<4	3 <u>27</u>	-	
SRAI	fraction is larger than 2.36 mm)	6 fine 2.36	GC	Clayey gravels, gravel-sand- clay mixtures (1)	a given in	12-50	Above 'A' line and PI>7	200	- 	(2) Borderline
8	SANDS		SW	Well graded sands and gravelly sands, little or no fines	he cateda	0-5	S=33	>6	Between 1 and 3	classifications occur when the percentage of fines (fraction
an half of	(more than half of coarse fraction is smaller than 2.36 mm)	0.6	SP	Poorly graded sands and gravelly sands, little or no fines	of fractions according to the	0-5	12 1 - 1 24		comply with	smaller than 0.075 mm size) is greater than 5% and less than 12%. Borderline
(more than half			SM	Silty sands, sand silt mixtures (1)	oris acco	12-50	Below 'A' line or PI<4	=	=	
			5 SC Clayey sands, sand-clay mixtures (1)		12-50	Above 'A' line and PI>7	-	_	classifications require the use of SP-SM, GW- GC.	
n 0.075 mm			ML	Inorganic silts, very fine sands, rock flour, silty or clayey fine sands or clayey silts with slight plasticity	For classification of fine grained so				ined soils	
LS is smaller than	SILTS & CLA (Liquid Limit:	200	CL	Inorganic clays of low to medium plasticity, gravelly clays, sandy clays, silty clays, lean clays	g 63 mm for	60			n or coarse gr	rained soils.
SOILS mm B			OL	Organic silts and clays of low plasticity	passin	80				100
FINE GRANED SOILS (more than half of material less than 83 mm is			МН	Inorganic silts, mic- aceous or diato-maceous fine sands or silts, elastic silts	gradation curve of material passing	Plastic Index (%)			4/	The Parties
	SILTS & CLAYS (Liquid Limit >50%) CH		Inorganic clays of high plasticity, fat clays	curve	2000	13/18/19	0	O MHR	26	
			ОН	Organic silts and clays of high plasticity	adation	10	Zen	-	.401	
	HIGHLY ORG	GANIC	PT	Peat and other highly organic soils	Use the gr	0	10 20	30 40 Liqu	se ee uid Limit (%)	70 80 90 100





Grain size analysis is performed by two processes depending on particle size. Sand silt and clay particles are assessed using a standardised hydrometer test, and coarse sand and larger is assessed through sieving by USCS certified sieves. For more detail see the following section.

Soil Classification	Particle Size	
Clay	Less than 0.002mm	
Silt	0.002 – 0.06mm	
Fine/Medium Sand	0.06 – 2.0mm	
Coarse Sand	2.0mm – 4.75mm	
Gravel	4.75mm – 60.00mm	

1.4 Bearing Capacities and DCP testing.

DCP and PSP weighted penetrometer tests – Dynamic Cone Penetrometer (DCP) and Perth Sand Penetrometer (PSP) tests are carried out by driving a rod into the ground with a falling weight hammer and measuring the blows for successive 100mm increments of penetration. Normally, there is a depth limitation of 1.2m but this may be extended in certain conditions by the use of extension rods. The methods for the two tests are quite similar.

- Dynamic Cone Penetrometer a 16mm rod with a 20mm diameter cone end is driven with a 9kg hammer dropping 510mm (AS 1289, Test 6.3.2).
- Perth Sand Penetrometer a 16mm diameter flat-ended rod is driven with a 9kg hammer, dropping 600mm (AS 1289 Test 6.3.3). This test was developed for testing the density of sands and is mainly used in granular soils and filling.

Site Anomalies – During construction GES will need to be notified of any major variation to the foundation conditions as predicted in this report.




Development Application: Development Application -Lot 30 Spoonbill Loop, Sorell - P1.pdf







1.5 Batter Angles for Embankments (Guide Only)







Glossary of Terms

Bearing Capacity – Maximum bearing pressure that can be sustained by the foundation from the proposed footing system under service loads which should avoid failure or excessive settlement.

Clay – (Mineral particles less than 0.002mm in diameter). Fine grained cohesive soil with plastic properties when wet. Also includes sandy clays, silty clays, and gravelly clays.

Dynamic Cone Penetrometer (DCP) – Field equipment used to determine underlying soil strength and therefore bearing capacity (kPa) by measuring the penetration of the device into the soil after each hammer blow.

Dispersive soil – A soil that has the ability to pass rapidly into suspension in water.

Footing – Construction which transfers the load from the building to the foundation.

Foundation – Ground which supports the building

Landslip – Foundation condition on a sloping site where downhill foundation movement or failure is a design consideration.

Qualified Engineer – A professional engineer with academic qualifications in geotechnical or structural engineering who also has extensive experience in the design of the footing systems for houses or similar structures.

Reactive Site – Site consisting of clay soil which swells on wetting and shrinks on drying by an amount that can damage buildings on light strip footings or unstiffened slabs. Includes sites classified as S, M, H-1, H-2 & E in accordance with AS2870-2011.

Sand – (Mineral particles greater than 0.02mm in diameter). Granular non-cohesive, non-plastic soil that may contain fines including silt or clay up to 15%.

Services – Means all underground services to the site including but not limited to power, telephone, sewerage, water & storm water.

Silt – (Mineral particles 0.002 - 0.02mm in diameter). Fine grained non-cohesive soil, non-plastic when wet. Often confers a silky smoothness of field texture, regularly includes clay and sand to form clayey silts, sandy silts and gravelly silts.

Site – The site title, as denoted by address, lot number, or Certificate of Title (CT) number, or Property Identification Number (PID).

Surface Movement (Ys) – Design movement (mm) at the surface of a reactive site caused by moisture changes.



Development Application: Development Application -Lot 30 Spoonbill Loop, Sorell - P1.pdf



Disclaimer

This Report has been prepared in accordance with the scope of services between Geo-Environmental Solutions Pty. Ltd. (GES) and the Client. To the best of GES's knowledge, the information presented herein represents the client's requirements at the time of printing of the Report. However, the passage of time, manifestation of latent conditions or impacts of future events may result in findings differing from that discussed in this Report. In preparing this Report, GES has relied upon data, surveys, analyses, designs, plans and other information provided by the Client and other individuals and organisations referenced herein. Except as otherwise stated in this Report, GES has not verified the accuracy or completeness of such data, surveys, analyses, designs, plans and other information.

The scope of this study does not allow for the review of every possible geotechnical parameter or the soil conditions over the whole area of the site. Soil and rock samples collected from the investigation area are assumed to be representative of the areas from where they were collected and not indicative of the entire site. The conclusions discussed within this report are based on observations and/or testing at these investigation points.

This report does not purport to provide legal advice. Readers of the report should engage professional legal practitioners for this purpose as required.

No responsibility is accepted for use of any part of this report in any other context or for any other purpose by third a party.



Development Application: Development Application -Lot 30 Spoonbill Loop, Sorell - P1.pdf








Site Plan







Development Application: Development Application -Lot 30 Spoonbill Loop, Sorell - P1.pdf







APPENDIX 1 - DCP Results Table

Dynamic Cone Penetration (DCP) Conversion to Californian Bearing Ratio (ref: Australian Standard AS 1289.6.3.2 - 1997)

DCP Location BH1

Depth (mm)	DCP	DCP	DCP Resistance	Allowable Bearing Capacity	CBR (Rounded Up)
	(Blows/100mm)	(mm/Blow)	(mPa)	(kPa)	
0-100	4	25.0	1.3	139	8
100-200	5	20.0	1.6	174	10
200-300	3	33.3	0.9	104	6
300-400	3	33.3	0.9	104	6
400-500	3	33.3	0.9	104	6
500-600	2	50.0	0.6	69	4
600-700	2	50.0	0.6	69	4
700-800	1	100.0	0.3	35	2
800-900	2	50.0	0.6	69	4
900-1000	2	50.0	0.6	69	4
1000-1100	5	20.0	1.6	174	10
1100-1200	6	16.7	1.9	208	13
1200-1300	8	12.5	2.5	278	17
1300-1400	7	14.3	2.2	243	15
1400-1500	6	16.7	1.9	208	13
1500-1600	6	16.7	1.9	208	13
1600-1700	9	11.1	2.8	313	20
1700-1800	12	8.3	3.8	417	27
1800-1900	14	7.1	4.4	486	32
1900-2000	19	5.3	5.9	660	45



Development Application: Development Application -Lot 30 Spoonbill Loop, Sorell - P1.pdf

CERTIFICATE OF QUALIFIED PERSON – ASSESSABLE ITEM

Section 321

То	: Wilso	n Homes				Owner /Agent				Ī
	250 N	Murray Stre	et			Address	Form	5	5	
	Hoba	ırt		70	00	Suburb/postcode				
Qualified pers	on deta	ails:								
Qualified person:	John	-Paul Cumr	mina							
Address:		rksway Pla				Phone No:	03	6223	1839	_
		ry Point		70	04	Fax No:				_
Licence No:	AO999	- -	Email address:	jcun	nming	@geosolutio	ns.net	.au		
Qualifications and Insurance details:	Scier	fied Profess	stage 2)		Directo by Qua Items	ption from Column or's Determination - alified Persons for A	Certificat ssessabi			
Speciality area of expertise:	1	370-2011 Fo	oundation		Directo	or's Determination - alified Persons for A	Certifica			
Details of wor	k:									
Address:	Lot 3	0 Pittwater	Shores Estate				Lot No:			_
	Sore	I		71	72	Certificate of t	title No:	TBC		
The assessable item related to this certificate:	_	sification of rding to AS	foundation Col 2870-2011	nditio	ns	(description of the certified) Assessable item i - a material; - a design - a form of con - a document - testing of a consystem or plu - an inspection performed	ncludes - struction omponen imbing sy	- nt, buildin vstem		
Certificate det	ails:									
Certificate type:	Founda	tion Classit	fication		Sch Dete Qua	ecription from Colum edule 1 of the Direct ermination - Certifica lified Persons for essable Items n)	tor's			
This certificate is	in relatior	n to the above	e assessable item	, at an	y stage	e, as part of - <i>(tic</i>	k one)			
	k		plumbing work or	plumb	oing ins	stallation or dem	nolition	work [\boxtimes	
ell Council Application: Developmen		or	a building, ten	nporar	y struc	ture or plumbino	q install	ation: [
Lot 30 Spoonbill Loop, So ence:P1 red:12/04/2024	rell - P1.pdf									

In issuing this certificate the following matters are relevant –

Documents: The attached soil report for the address detailed above in 'details of

work'

Relevant

calculations: Reference the above report.

References: AS2870:2011 residential slabs and footings

AS1726:2017 Geotechnical site investigations

CSIRO Building technology file - 18.

Substance of Certificate: (what it is that is being certified)

Site Classification consistent with AS2870-2011.

Scope and/or Limitations

The classification applies to the site as inspected and does not account for future alteration to foundation conditions as a result of earth works, drainage condition changes or variations in site maintenance.

I, John-Paul Cumming certify the matters described in this certificate.

Qualified person:

Signed:

Certificate No:

J10016

Date:

08/03/2024







Development Application: Development Application -Lot 30 Spoonbill Loop, Sorell - P1.pdf



28 Suncrest Avenue Lenah Valley, TAS 7008 mark@ecotas.com.au www.ecotas.com.au 0407 008 685 ABN 83 464 107 291

Sorell Council

Development Application:Response to Request for Information - 8 Spoonbill Loop, Sorell (Lot 30).pdf Plan Reference:P3 Date received:12/07/2024

12 July 2024

Wilson Homes Tasmania Pty Ltd

ATTENTION: Sonya Gadd (Project Coordinator) 250 Murray Street

Hobart TAS 7000

Dear Sonya

RE: 8 (Lot 30) Spoonbill Loop, Sorell (PID 9066476; C.T. 187106/30)

Proposed Development/Use - Single Residential Dwelling

Preamble

I refer to engagement to assess the natural values of 8 (Lot 30) Spoonbill Loop, Sorell, specifically to address matters likely to be requested by Sorell Council as part of a planning application in relation to C7.6.1 P1.1 & P1.2 of the Natural Assets Code of the Tasmanian Planning Scheme - Sorell Local Provisions Schedule (understood to be lodged and now recognised as 5.2024.72.1).

It is noted the Priority Vegetation Area overlay is also present across the title, but because the title is zoned as General Residential the Natural Assets Code has no application in relation to this overlay.

Site details

Address: 8 (Lot 30) Spoonbill Loop, Sorell PID: 9066476; C.T.: 187106/30; LPI: JWE56

Zone: General Residential

Overlays (relevant to the present assessment): Waterway and Coastal Protection Area (Natural

Assets Code) - see notes below

The overlay is 100 m wide, but set well back from the high tide mark. It is assumed that the overlay is related directly to the presence of the Ramsar wetland referred to as Pitt Water-Orielton Lagoon.

Area: measured area = 470 m^2 [source: LISTmap]

Topography: flat terrain.

Current land use: previous disused pasture now developed as completely developed as a residential subdivision, with all roads and services already approved and constructed (Plates 1-4)

Drainage features: none present



Plate 1. (LHS) Current land use of Lot 30 Spoonbill Loop showing wholly cleared land with no native vegetation present

Plate 2. (RHS) Existing formed access and services of Lot 30 Spoonbill Loop



Plate 3. (LHS) View along Spoonbill Loop showing fully developed subdivision with all services provided **Plate 4.** (RHS) Example of existing service along Spoonbill Loop

Proposal

The proposal is for a single residential dwelling.

Assessment

Preliminary database checks

LISTmap was examined to determined existing vegetation mapping and known sites for threatened flora and fauna. Database reports were produced under DNRET's *Natural Values Atlas*, the Forest Practices Authority's *Biodiversity Values Database* and the Commonwealth *Protected Matters Report* to support the assessment process.

Site assessment

I attended the site on 11 Jul. 2024.

Findings

Vegetation types

All versions of TASVEG (3.0, 4.0 & Live) indicate the subject title is mapped as urban areas (TASVEG code: FUR), correctly reflecting the current status of the land i.e. there is no need for a revised vegetation map as the site is now wholly developed for sale and occupation of small lots.

Threatened flora

Database information indicates that the subject title does not support known populations of flora listed as threatened on either the Tasmanian *Threatened Species Protection Act 1995* or the Commonwealth *Environment Protection and Biodiversity Protection Act 1999*. Site assessment did not detect any such species.

Threatened fauna

Database information indicates that the subject title does not support known populations of fauna listed as threatened on either the Tasmanian *Threatened Species Protection Act 1995* or the Commonwealth *Environment Protection and Biodiversity Protection Act 1999*. Site assessment did not detect any such species, nor significant potential habitat of such species.

Consideration of planning scheme requirements

The Purpose of the Natural Assets Code is stated as:

- C7.0 Natural Assets Code
- C7.1 Code Purpose

The purpose of the Natural Assets Code is:

- C7.1.1 To minimise impacts on water quality, natural assets including native riparian vegetation, river condition and the natural ecological function of watercourses, wetlands and lakes.
- C7.1.2 To minimise impacts on coastal and foreshore assets, native littoral vegetation, natural coastal processes and the natural ecological function of the coast.
- C7.1.3 To protect vulnerable coastal areas to enable natural processes to continue to occur, including the landward transgression of sand dunes, wetlands, saltmarshes and other sensitive coastal habitats due to sea-level rise.
- C7.1.4 To minimise impacts on identified priority vegetation.
- C7.1.5 To manage impacts on threatened fauna species by minimising clearance of significant habitat.

RESPONSE: Of these purpose statements, C7.1.1 & C7.1.2 have the most relevant application as the overlay is directly related to the adjacent Ramsar wetland.



The Code has the following application:

- C7.2 Application of this Code
- C7.2.1 This code applies to development on land within the following areas:
 - (a) a waterway and coastal protection area;
- C7.2.2 This code does not apply to use.

RESPONSE: C7.2.1(a) is applicable.

The Development Standards for Buildings and Works (C7.6) and specifically those for Buildings and Works within a Waterway and Coastal Protection Area or Future Coastal Refugia Area (last not relevant) are stated below:

- C7.6 Development Standards for Buildings and Works
- C7.6.1 Buildings and works within a waterway and coastal protection area or a future coastal refugia area

Objective: That buildings and works within a waterway and coastal protection area or future coastal refugia area will not have an unnecessary or unacceptable impact on natural assets.

RESPONSE: While there will be works within the technical overlay it is very difficult to anticipate a scenario in which such works would "have an unnecessary or unacceptable impact on natural assets" given the wholly modified status of the title. The title is one of several small new titles released on previously farmed land, wholly approved by Sorell Council for the primary purpose of residential development, with roads and services all already established. Spoonbill Loop is fully sealed and furnished with sealed concrete footpaths and drains adjacent to the title. It is a reasonable assumption that the approval of the subdivision took due account of the potential direct and/or indirect immediate and/or future impacts on the adjacent Ramsar wetland. That is, I do not find the intent of the objective statement will be compromised by the now proposed development.

The Acceptable Solution A1 of C7.6.1 is stated as:

Α1

Buildings and works within a waterway and coastal protection area must:

- (a) be within a building area on a sealed plan approved under this planning scheme;
- (b) in relation to a Class 4 watercourse, be for a crossing or bridge not more than 5 m in width; or
- (c) if within the spatial extent of tidal waters, be an extension to an existing boat ramp, car park, jetty, marina, marine farming shore facility or slipway that is not more than 20% of the area of the facility existing at the effective date.

RESPONSE: In my interpretation, these provisions are either not met or are not applicable, noting that A1(a) refers to "this planning scheme" and so I presume any approval of the now older subdivision and obviously any subsequent development under the previous scheme is no longer applicable.

The Performance Criteria P1.1 of C7.6.1 is stated as:

P1.1

Buildings and works within a waterway and coastal protection area must avoid or minimise adverse impacts on natural assets, having regard to:

RESPONSE: Under the Code, "natural assets" are taken to mean "biodiversity, environmental flows, natural stream bank and stream bed condition, riparian vegetation, littoral vegetation, water quality, wetlands, river condition and waterway and/or coastal values" i.e. they have broad definition and potential application. That said, in this case the highly modified status of

the title is reiterated but noting the overlay refers more relevantly to the adjacent Ramsar wetland.

As a starting point, the opening phrase of P1.1 refers to "...must avoid or minimise adverse impacts on natural assets...". The use of the term "minimise" contemplates a level of acceptable impact, although this is not defined anywhere. On the basis that the lot is very small and clearly intended for residential development (and already approved as such by the planning authority), combined with the absence of "natural assets" per se within and adjacent to the title (existing wholly cleared land), in my opinion, the project achieves the objective to "minimise adverse impacts" as far as practicable.

With respect to the phrase "...having regard to...", this is considered in the manner referred to in *S and S McElwaine and A Hamilton v West Tamar Council and Growth Developments Pty Ltd [2021] TASCAT 4 (17 November 2021)*, where TASCAT stated: "the requirement to 'have regard to' does not elevate P2.1(a) to (f) to mandatory requirements that the proposal must satisfy. The tribunal need only consider those subparagraphs in ascertaining whether the proposal complies with clause E8.6.1 P2.1".

Below the sub-criteria of P1.1 are addressed in turn.

(a) impacts caused by erosion, siltation, sedimentation and runoff;

RESPONSE: To my interpretation, this provision is either not applicable or met by default because there should be limited impacts caused by erosion, siltation, sedimentation and runoff into adjacent areas (noting P1.1 requires impacts to be "avoided <u>or</u> minimised"). Based on my site assessment, I struggle to understand that routine construction works that now require a 6-foot fence to be placed around the construction zone would not appropriately manage this risk. It is further noted that the site is on the far eastern side of this approved subdivision, separated from the reserve by two sealed parts of Spoonbill Loop and three lines of lots ready for development, the western section largely already fenced between the lots and the coastal reserve.

(b impacts on riparian or littoral vegetation;

RESPONSE: Not applicable because there is no proposal to impact on littoral vegetation with all works intended to be wholly within the existing cleared title. Riparian vegetation is not present.

(c) maintaining natural streambank and streambed condition, where it exists;

RESPONSE: Not applicable (site does not support any watercourses).

(d) impacts on in-stream natural habitat, such as fallen logs, bank overhangs, rocks and trailing vegetation;

RESPONSE: Not applicable (site does not support any watercourses).

(e) the need to avoid significantly impeding natural flow and drainage;

RESPONSE: Not applicable (site does not support any watercourses).

(f) the need to maintain fish passage, where known to exist;

RESPONSE: Not applicable (site does not support any watercourses).

(g) the need to avoid land filling of wetlands;

RESPONSE: Not applicable – there is no intention to impact on the wetland in any manner (specifically, no proposal to "land fill" this feature).

(h) the need to group new facilities with existing facilities, where reasonably practical;

RESPONSE: To my interpretation, this provision is either not applicable.

(i) minimising cut and fill;

RESPONSE: To my interpretation, this provision is satisfied as there will be limited cut and fill (flat terrain).



(j) building design that responds to the particular size, shape, contours or slope of the land;

RESPONSE: To my interpretation, this provision is satisfied based on the site plans provided, noting this is an approved subdivision that permitted a ca. 470 m² title, with no practical options to position a dwelling.

(k) minimising impacts on coastal processes, including sand movement and wave action;

RESPONSE: In my opinion, provided works are restricted to the title itself, there should be no impact on coastal processes because the site is well above the high water mark and set well back from this mark separated from the reserve by two sealed parts of Spoonbill Loop and three lines of lots ready for development, the western section largely already fenced between the lots and the coastal reserve.

(I) minimising the need for future works for the protection of natural assets, infrastructure and property;

RESPONSE: In my opinion, this provision has little practical application to a very small title where works will be wholly contained within the title.

(m) the environmental best practice guidelines in the *Wetlands and Waterways Works Manual*; and

RESPONSE: Not applicable (there will be no works that will manifestly impact on wetlands or waterways).

(n) the guidelines in the Tasmanian Coastal Works Manual

RESPONSE: In my opinion, this manual will have little direct application to the present scenario provided that works are wholly restricted to the title itself.

Based on the above review of P1.1 of C7.6.1, the proposal will fully satisfy all relevant provisions without the need for specific mitigation conditions.

Further consideration of Ramsar wetland

With specific reference to the Ramsar wetland, which is considered to be a Matter of Environmental Significance under the Commonwealth *Environment Protection and Biodiversity Protection Act 1999*, the *Information Sheet on Ramsar Wetlands (RIS) – 2009-2014 version* (CofA 2014) provides extensive background on the Pitt Water – Orielton Lagoon Ramsar site. Under Section 26 (Factors (past, present or potential) adversely affecting the site's ecological character, including changes in land (including water) use and development projects) and specifically under "(b) – factors in the surrounding area", the following information is provided:

"Increasing numbers of subdivisions on the shores of Orielton Lagoon and Midway Point may contribute to increased run-off and sediments. Subdivisions can result in additional stormwater outlets, potential for dumping and spread of weed species, and general disturbance from noise, pets, and human activity. Some of the stormwater is partially treated. Some treatments allow only for the removal of solid pollutants such as litter, while others also reduce sediment and nutrient loads. Stormwater remains an increasing source of nutrients and a significant threat to the environmental quality of Orielton Lagoon.

During 2013/14 leakage from old or damaged sewage infrastructure caused the temporary closure of Oyster farms in Pitt Water area to limit potential public health risk.

Irrigation practices, stock management and ground water manipulation on adjacent agricultural land impact on saltmarshes, seagrass, hydrology, sediment and water quality. Gully erosion, prevalent around Orielton Lagoon, can contribute sediment straight into the wetland. In addition to sedimentation, runoff from planted croplands, pastures and other agricultural areas with high fertiliser use may also contribute to increased nutrient loads in wetland. Nutrient (nitrogen, nitrate and phosphorus) levels in the Coal River are generally at low levels, however, a few high flow events can carry the majority of annual nutrient load (Gallagher 1998).

New developments such as the construction of the South East Irrigation Scheme will increase the amount and type of agricultural cropping in the catchment.

8 (Lot 30) Spoonbill Loop, Sorell: Natural Values Statement

The modification of the runways at Cambridge Airport in 2013 has the potential for increased storm water and industrial runoff to the site.

There are a number of proposed developments near the site (e.g. runway extension for Hobart International Airport; new golf course and large residential development at Seven Mile Beach, industrial complex at Barilla Bay) have the potential for increased storm water, industrial runoff, nutrient load and disturbance to bird values of site.

One of the biggest threats to the Pitt Water estuary is likely to be climate change through rising sea level and altered water balance in the catchment area. Inundation of low-lying areas may occur, with erosion and recession of sandy beaches (causing narrowing of the spit), and landward growth and translation of the marine tidal delta".

It is assumed that the approval of the subdivision took due account of the potential direct and/or indirect immediate and/or future impacts on the adjacent Ramsar wetland meaning that lot-by-lot consideration should not be warranted. In this case, the status of the land and its context (ex-pasture now fully roaded and serviced and separated from the reserve by two sealed parts of Spoonbill Loop and three lines of lots ready for development, the western section largely already fenced between the lots and the coastal reserve) means that impacts to the wetland from works within the title will be negligible.

Under the Commonwealth *Environment Protection and Biodiversity Conservation Act 1999* an action will require approval from the minister if the action has, will have, or is likely to have, a significant impact on a matter of national environmental significance.

Matters of national environmental significance considered under the EPBCA include:

- listed threatened species and communities
- listed migratory species;
- Ramsar wetlands of international importance;
- · Commonwealth marine environment;
- world heritage properties;
- national heritage places;
- the Great Barrier Reef Marine Park;
- nuclear actions; and
- a water resource, in relation to coal seam gas development and large coal mining development.

The relevant Commonwealth agency provides a policy statement titled *Matters of National Environmental Significance: Significant Impact Guidelines 1.*1 (CofA 2013, herein the *Guidelines*), which provides overarching guidance on determining whether an action is likely to have a significant impact on a matter protected under the EPBCA.

The Guidelines define a significant impact as:

"...an impact which is important, notable, or of consequence, having regard to its context or intensity. Whether or not an action is likely to have a significant impact depends upon the sensitivity, value, and quality of the environment which is impacted, and upon the intensity, duration, magnitude and geographic extent of the impacts"

and note that:

"...all of these factors [need to be considered] when determining whether an action is likely to have a significant impact on matters of national environmental significance".

The Guidelines provide advice on when a significant impact may be likely:

"To be 'likely', it is not necessary for a significant impact to have a greater than 50% chance of happening; it is sufficient if a significant impact on the environment is a real or not remote chance or possibility.

If there is scientific uncertainty about the impacts of your action and potential impacts are serious or irreversible, the precautionary principle is applicable. Accordingly, a lack of scientific certainty



about the potential impacts of an action will not itself justify a decision that the action is not likely to have a significant impact on the environment".

The *Guidelines* provide a set of Significant Impact Criteria, which are "intended to assist...in determining whether the impacts of [the] proposed action on any matter of national environmental significance are likely to be significant impacts". It is noted that the criteria are "intended to provide general guidance on the types of actions that will require approval and the types of actions that will not require approval...[and]...not intended to be exhaustive or definitive".

In relation to Ramsar wetlands, the *Guidelines* provide the following information:

Indirect and offsite impacts

When considering whether or not an action is likely to have a significant impact on a matter of national environmental significance it is relevant to consider all adverse impacts which result from the action, including indirect and offsite impacts.

Indirect and offsite impacts include:

- a. 'downstream' or 'downwind' impacts, such as impacts on wetlands or ocean reefs from sediment, fertilisers or chemicals which are washed or discharged into river systems;
- b. 'upstream impacts' such as impacts associated with the extraction of raw materials and other inputs which are used to undertake the action; and
- c. 'facilitated impacts' which result from further actions (including actions by third parties) which are made possible or facilitated by the action. For example, the construction of a dam for irrigation water facilitates the use of that water by irrigators with associated impacts. Likewise, the construction of basic infrastructure in a previously undeveloped area may, in certain circumstances, facilitate the urban or commercial development of that area.

Consideration should be given to all adverse impacts that could reasonably be predicted to follow from the action, whether these impacts are within the control of the person proposing to take the action or not. Indirect impacts will be relevant where they are sufficiently close to the proposed action to be said to be a consequence of the action, and they can reasonably be imputed to be within the contemplation of the person proposing to take the action.

It may be helpful to consider the following:

- 'But for' the proposed action would the indirect impacts occur?
- Is the proposed action a 'material and substantial' cause of the indirect impacts?
- Are the potential impacts of any subsequent or third party actions known, or would they be expected to be known, by the person proposing to take the action (particularly where the subsequent or third party actions are an intended outcome of the proposed action)?


If the answer to these questions is 'yes', then it is necessary to consider whether these impacts are likely to occur, and whether they are likely to have a significant impact on a matter of national environmental significance. If so, as much information as possible should be provided to assist the minister in determining whether the impacts are relevant, and whether approval under the EPBC Act is required.

In specific respect to wetlands of internal importance (Ramsar), the Guidelines state:

Approval is required for an action occurring within or outside a declared Ramsar wetland if the action has, will have, or is likely to have a significant impact on the ecological character of the Ramsar wetland.

An action is likely to have a significant impact on the ecological character of a declared Ramsar wetland if there is a real chance or possibility that it will result in:

- areas of the wetland being destroyed or substantially modified
- a substantial and measurable change in the hydrological regime of the wetland, for example, a substantial change to the volume, timing, duration and frequency of ground and surface water flows to and within the wetland
- the habitat or lifecycle of native species, including invertebrate fauna and fish species, dependant upon the wetland being seriously affected



8 (Lot 30) Spoonbill Loop, Sorell: Natural Values Statement

- a substantial and measurable change in the water quality of the wetland for example, a substantial change in the level of salinity, pollutants, or nutrients in the wetland, or water temperature which may adversely impact on biodiversity, ecological integrity, social amenity or human health, or
- an invasive species that is harmful to the ecological character of the wetland being established (or an existing invasive species being spread) in the wetland.

RESPONSE: Based on the site assessment, I do not consider that any of these potential impacts are likely such that a significant impact is not anticipated.

Note that this statement does not constitute legal advice, and provides my interpretation of the provisions of the *Tasmanian Planning Scheme – Sorell Local Provisions Schedule*, which may not represent the views of Sorell Council. It is recommended that formal advice be sought from the relevant agency prior to acting on any aspect of this report.

Please do not hesitate to contact me further if additional information is required.

Kind regards

Mark Wapstra

Senior Scientist/Manager

M Cypston



SW manhole I.V. in 2.78 I.V. out 2.77 Sewer line 261°06'00" 28.50 +4.48 Phone & power T connections Sewer (I.V. 2.71) & SW (I.V. 3.12) **+**4.57 ◆ connections Stopvalve Stopvalve Lot 30 Water connection 470m² SW manhole I.V. in 2.89 I.V. out 2.89 4.45 Sewer manhole I.V. in 1.77 I.V. out 1.73 Pipeline & Services, & Drainage Easement 'C' 3.50 wide

A B.M. Rivet in kerb R.L. 5.03 A.H.D.

Spoonbill

Wilson Multi, Lot 30 Spoonbill Loop, Sorell.

Detail Plan Lot 30

	SCALE		COI	NTOUR INTERVAL
1	:200	(@ A3)	0.1 metre	
	DATUM		File#	
Horiz.	MGA20		5727	
Vert.	A.H.D.			• · - ·
Surveyed	P.J.I	M.	Date	15-02-24
Autocad file	5727 Wilson Multi Lot 30 Spoonbill Loop			
GeoCivil file	5727\Detail\1\project\5727d1g20			

James McEldowney Surveying

15 Ingram Street, South Hobart. 7004.
Telephone (03) 62235236 Mobile 0418135442
Email: mail@jmsurvey.com.au

Sorell Council

Development Application: Development Application -Lot 30 Spoonbill Loop, Sorell - P1.

Plans Reference:P1 Date Received:12/04/2024

Note:Boundaries shown hereon are from preliminary plans.


Before commencement of any building work boundaries shown hereon should be verified by comparison with the final registered title dimensions as obtained from the Lands Titles Office.

James McEldowney Surveying accepts no responsibility for alterations made to preliminary plans prior to final registration.

Do not remove this note from this or subsequent plans.



Rcomplete BY WILSON HOMES



WH713965 - PROPOSED RESIDENCE Lot 30, Spoonbill Loop, SORELL

SHEET	DRAWING TITLE
01	SITE PLAN
01a	DRAINAGE PLAN
02	FLOOR PLAN
03	ELEVATIONS SHEET
03a	PERSPECTIVE VIEWS
03b	INTERNAL ELEVATIONS - KITCHEN
03c	INTERNAL ELEVATIONS - BATH
03d	INTERNAL ELEVATIONS - ENSUITE



velopment Application: Development pplication -Lot 30 Spoonbill Loop, Sorell - P1.pdf

Plans Reference:P1 Date Received:12/04/2024

DESIGN	YORK 14
FAÇADE	TEMPO

Client / Project info PROPOSED RESIDENCE

Lot 30, Spoonbill Loop,

SITE IS NOT BUSHFIRE PRONE AREA AS PER TASMANIAN PLANNING SCHEME OVERLAY - SORELL. No additional restrictions for construction methods / materials apply.

	DA PLAN SET	10 Apr. 24	ST	CK	01 - 03
	PRELIM DA PLAN SET	18 Mar. 24	ST	CK	01 - 03
No.	Amendment	Date	Drawn	Checked	Sheet

•	levels on site prior to commencement of
•	All work to be carried out in accordance with the current National Construction Co
•	All materials to be installed according to manufacturers specifications.
	Do not scale from these drawings. No changes permitted without consultation

ANOTHER PERSPECTIVE PTY LTD
PO BOX 21
NEW TOWN
LIC. NO. 685230609 (S. Turvey)
Ph: (03) 6231 4122
Fx: (03) 6231 4166
Email:


info@anotherperspective.com.au

Designer:


Soil Classification:
Title Reference:
Floor Areas:
Porch / Deck Areas:
Wind Speed:
Climate Zone:
Alpine Zone:
Corrosion Environmen
Certified BAL:
Designed BAL:

Soil Classification:	р
Title Reference:	TBC
Floor Areas:	154.73m²
Porch / Deck Areas:	16.23m²
Wind Speed:	N3
Climate Zone:	7
Alpine Zone:	N/A
Corrosion Environment:	Medium
Certified BAL:	NOT BUSHFIRE PRONE
Designed BAL:	NOT BUSHFIRE PRONE
(Refer to Standard Notes for Explanation)	

	COVER SHEET			
		WH713965		
Date	18 March 2024	Sheet		
Scale		00/03		
		00/03		



Ground Floor FFL 4.90 Garage FFL 4.83



B.M. Rivet in **∆** kerb R.L. 5.03 A.H.D.



evelopment Application: Development pplication -Lot 30 Spoonbill Loop, Sorell - P1.pdf

Plans Reference:P1 Date Received:12/04/2024

Boundaries shown hereon are from preliminary plans. Before commencement of any building work boundaries shown hereon should be verified by comparison with the final registered title dimensions as obtained from the Lands Titles Office. James McEldowney Surveying accepts no responsibility for alterations made to preliminary plans prior to final registration. Do not remove this note from this or subsequent plans.

SW manhole I.V. in 2.78 I.V. out 2.77

8m 1:200

EXPLANATORY NOTES: TASMANIAN PLANNING SCHEME - SORELL

8.4.3 - Site coverage and private open space for all dwellings

Site Coverage: Max. 50% of site = 235.00m² Proposed site coverage (excl. eaves up to 0.6m): 176.34m² (37.52%)

 Builder to verify all dimensions and levels on site prior to commencement of work

 All work to be carried out in accordance with the current National Construction Code. · All materials to be installed according to

manufacturers specifications. • Do not scale from these drawings.

No changes permitted without consultation with designer.

ANOTHER PERSPECTIVE PTY LTD PO BOX 21 NEW TOWN LIC. NO. 685230609 (S. Turvey) Ph: (03) 6231 4122 Fx: (03) 6231 4166

info@anotherperspective.com.au

Client / Project info

SORELL

Designer:


PROPOSED RESIDENCE **R**complete Lot 30, Spoonbill Loop,

	SITE PL	.AN
Drawn	ST	WH713965
Date	18 March 2024	Sheet
Scale	1:200	1 01/
		1 (<i>)</i> [/

No.


Date

Int. Amendment changes as per cover sheet




Where ag drain is \leq 1.5m from footing, the following engineering principles are required:

- 1. Ag drain to be capped with 300mm of clay to prevent ingress of surface run-off unless it is under a paving slab etc (ag drains are designed for removal of ground water, surface water should be dealt with separately).
- 2. Ag drain to have a minimum 1% fall to a grated pit which drains to the stormwater system.
- 3. Install a geotextile filter sock to the slotted drain, and enclose the whole drain in geofabric (to the underside of clay capping).
- 4. Provide additional grated pits / or inspection openings along the length of the ag drain and at the high point to make the effect of a blockage visible and enable a blockage to be cleared.




TYPICAL AG. DRAIN DETAIL (<1800 FROM HOUSE) Not to scale



TYPICAL AG. DRAIN DETAIL (≥1800 FROM HOUSE) Not to scale

No.

Date



Boundaries shown hereon are from preliminary plans.

Before commencement of any building work boundaries shown hereon should be verified by comparison with the final registered title dimensions as obtained from the Lands Titles Office. James McEldowney Surveying accepts no responsibility for alterations made to preliminary plans prior to final registration.


Do not remove this note from this or subsequent plans.



ment Application: Development application -Lot 30 Spoonbill Loop, Sorell - P1.pd

Plans Reference:P1 ate Received:12/04/2024

Client / Project info



DRAINAGE LEGEND

. Flexible connections are to be installed on any pipes emerging from beneath the building in accordance with AS2870 & AS/NZS3500.2:2021.

- Untrapped Bath tub pipe to connect to FWG if trap not accessible from below or access panel. 3. 50Ø required for multiple shower heads.
- 4. Showers to comply with N.C.C. 10.2.14.
- 5. Falls to floor waste to be minimum 1:80 & maximum 1:50

B.M. Rivet in **△** kerb R.L. 5.03 A.H.D.

Spoonbill

Refer to Roof Plan for downpipe calculations

All works are to in accordance with the Water Supply Code of Australia WSA 03-2011-3.1 Version 3.1 MRWA Edition V2.0 and Sewerage Code of Australia Melbourne Retail Water Agencies Code WSA 02-2014-3.1 MRWA Version 2.0 and TasWater's supplements to these codes.

ROOF DRAINAGE NOTE:

Min. medium rectangular gutter & min. 90ø downpipe specified as per N.C.C. part 7.4. These sizes and downpipe quantities are based on a max. roof catchment area of 70m²

> 8m 1:200

Soil classification: Refer to Soil Report for nominated founding depth and description of founding material All Materials and construction to comply with

- Wet areas to comply with NCC 10.2 and AS3740

- Builder to verify all dimensions and levels on site prior to commencement of work
- All work to be carried out in accordance with the current National Construction Code. All materials to be installed according to
- manufacturers specifications.
- · Do not scale from these drawings. · No changes permitted without consultation with designer.

ANOTHER PERSPECTIVE PTY LTD PROPOSED RESIDENCE PO BOX 21 Lot 30, Spoonbill Loop, NEW TOWN SORELL LIC. NO. 685230609 (S. Turvey) Ph: (03) 6231 4122 Fx: (03) 6231 4166

Rcomplete

	DRAINAGE	PLAN
Drawn	ST	WH713965
Date	10 April 2024	Sheet
Scale	1:200	N1a/0
		1 U I d/ (


AS/NZ3500 Part 2 & Part 3


Int. Amendment changes as per cover sheet


Designer:


info@anotherperspective.com.au














Development Application: Development Application -Lot 30 Spoonbill Loop, Sorell - P1.pdf

Plans Reference:P1 Date Received:12/04/2024

No.

Date



info@anotherperspective.com.au

Floor Area = 154.73m²

Articulation joints

Smoke Alarm (inte

than 1)

Int. Amendment changes as per cover sheet

Smoke Alarm (interconnected where more

All window sizes to be checked and/or confirmed on site prior to ordering glazing units

- Notes
 Builder to verify all dimensions and
- levels on site prior to commencement of work

 All work to be carried out in accordance
- with the current National Construction Code.

 All materials to be installed according to manufacturers specifications.
- Do not scale from these drawings.
 No changes permitted without consultation with designer.


Designer: Client / Project info


ANOTHER PERSPECTIVE PTY LTD
PO BOX 21
NEW TOWN
LIC. NO. 685230609 (S. Turvey)
Ph: (03) 6231 4122
Fx: (03) 6231 4166
Email:


Recomplete Dr. By WILSON HOMES SC

	FLOOR PLAN						
	Drawn	ST	WH713965				
>	Date	18 March 2024	Sheet				
\$	Scale	1:100	N2/N2				
		Copyright ©	02/03				

4m










Development Application: Development Application -Lot 30 Spoonbill Loop, Sorell - P1.pdf


Plans Reference:P1 Date Received:12/04/2024


No.


Date

	Notes - Builder to verify all dimensions and levels on site prior to commencement of work	Designer:	Client / Project info		PERSPECTIV	'E VIEWS
Int. Amendment changes as per cover sheet Shadows shown for stylisations purpose only	All work to be carried out in accordance with the current National Construction Code. All materials to be installed according to manufacturers specifications. Do not scale from these drawings. No changes permitted without consultation with designer.	ANOTHER PERSPECTIVE PTY LTD PO BOX 21 NEW TOWN LIC. NO. 685230609 (S. Turvey) Ph: (03) 6231 4122 Fx: (03) 6231 4166 Email: info@anotherperspective.com.au	PROPOSED RESIDENCE Lot 30, Spoonbill Loop, SORELL	Recomplete BY WILSON HOMES	Date 18 March 2024	WH713965 Sheet 03a/03









LEGEND: MWS - MICROWAVE SPACE DWS - DISHWASHER SPACE

RS - REFRIGERATOR SPACE

- DIMENSIONS ARE FROM STUD WALL - NOT FINISHED SURFACES

Kitchen Internal Elevation B



Int. Amendment changes as per cover sheet

No.


Date


Kitchen Internal Elevation D

Pantry


902

DWS








Bath Internal Elevation A



Bath Internal Elevation D







LEGEND - RAIL SHOWER RSHR ROSE - SHOWER ROSE ELBW - SHOWER ELBOW CONNECTION - MIXER TAP MIX - HOT TAP - COLD TAP - HOB SPOUT - WALL SPOUT - STOP COCK TRH - TOILET ROLL HOLDER TR-S - TOWEL RAIL-SINGLE TR-D - TOWEL RAIL-DOUBLE - TOWEL LADDER - TOWEL RACK TMB - TUMBLER HOLDER RNG - TOWEL RING - ROBE HOOK SHLF - SHELF

DIMENSIONS ARE FROM STUD WALL - NOT FINISHED SURFACES



info@anotherperspective.com.au



No.

Date

Sorell Council

evelopment Application: Development pplication -Lot 30 Spoonbill Loop, Sorell - P1.pdf

Int. Amendment changes as per cover sheet

 Builder to verify all dimensions and levels on site prior to commencement of work

 All work to be carried out in accordance with the current National Construction Code.

 All materials to be installed according to manufacturers specifications.


· Do not scale from these drawings.


No changes permitted without consultation with designer.

Client / Project info Designer: ANOTHER PERSPECTIVE PTY LTD PROPOSED RESIDENCE PO BOX 21 Lot 30, Spoonbill Loop, NEW TOWN LIC. NO. 685230609 (S. Turvey) Ph: (03) 6231 4122 Fx: (03) 6231 4166


RecompleteBY WILSON HOMES

INTERNAL ELEVATIONS - BATH							
Drawn	ST	WH713965					
Date	18 March 2024	Sheet					
Scale	1:50	03~/03					
	Copyright ©	03c/03					







Ensuite Internal Elevation D



Ensuite Internal Elevation B






Ensuite Internal Elevation C



Int. Amendment changes as per cover sheet



	Notes	
•	Builder to verify all dimensions and	

- levels on site prior to commencement of work

 All work to be carried out in accordance with the current National Construction Code.
- All materials to be installed according to manufacturers specifications.
- Do not scale from these drawings.
- No changes permitted without consultation with designer.


,	Designer:	Client / Project info
`	ANOTHER PERSPECTIVE PTY LTD PO BOX 21 NEW TOWN LIC. NO. 685230609 (S. Turvey) Ph: (03) 6231 4122 Fx: (03) 6231 4166 Email: info@anotherperspective.com.au	PROPOSED RESIDENCE Lot 30, Spoonbill Loop, SORELL

Rcomplete	
BY WILSON HOMES	

RSHR	- RAIL SHOWER
ROSE	- SHOWER ROSE
ELBW	- SHOWER ELBOW CONNECTION
MIX	- MIXER TAP
HT	- HOT TAP
CT	- COLD TAP
HS	- HOB SPOUT
WS	- WALL SPOUT
SC	- STOP COCK
TRH	- TOILET ROLL HOLDER
TR-S	- TOWEL RAIL-SINGLE
TR-D	- TOWEL RAIL-DOUBLE
TL	- TOWEL LADDER
TR	- TOWEL RACK
TMB	- TUMBLER HOLDER
RNG	- TOWEL RING
RH	- ROBE HOOK
SHLF	- SHELF
	INS ARE FROM STUD WALL - NOT SURFACES

LEGEND

	INTERNAL ELEVATIONS -							
	ENSUITE							
e HOMES	Drawn	ST	WH713965					
	Date	18 March 2024	Sheet					
	Scale	1:50	U34/U3					
		Copyright ©	U3U/U3					



LEGEND (W = Wattage e.g. 35W = 35 Watts.)

STANDARD CEILING LIGHT POINT (30W)

DOWNLIGHT POINT (UNVENTED) (35W)

LED DOWNLIGHT POINT (10W) SUITABLE FOR & FITTED WITH INSULATION OVER. (IC RATED)

PENDANT LIGHT (30W)

WALL LIGHT POINT (30W)

2 x 900mm FLUORESCENT LIGHT POINT (36W)

2 x SLIM T5 900mm FLUORESCENT LIGHT POINT (28W)

SINGLE POWER POINT \triangle

DOUBLE POWER POINT

DOUBLE POWER POINT WITH USB

WATER PROOF POWER POINT

MAINS POWERED SMOKE ALARM (INTERCONNECTED WHERE MORE THAN 1)

FAN / HEATER / LIGHT (8W) (VENT IN ACCORDANCE WITH N.C.C. 10.8.2)

TV CONNECTION POINT

NBN/TELEPHONE CONNECTION POINT

 \mathbb{M}

 \bigvee

EXHAUST FAN (VENT IN ACCORDANCE WITH N.C.C. 10.8.2)

 \square FLOOD LIGHT

CAT 6 CONNECTION POINT

TREAD LIGHTS (2W)

DUCTED VACUUM POINT

SECURITY SYSTEM KEYPAD

SECURITY SYSTEM SENSOR

25 L/s for a bathroom or sanitary compartment, 40 L/s for a kitchen or laundry. Exhaust from a kitchen, kitchen range hood, bathroom, sanitary compartment, or laundry must be discharged directly or via a shaft or duct to outdoor air.

Where no external ventilation / windows provided, exhaust fans to wet areas/ laundry to be fitted with a run on timer. 20mm gap base of door to comply with N.C.C. 10.8.2 (5)(a).



Development Application: Development Application -Lot 30 Spoonbill Loop, Sorell - P1.pdf

Int. Amendment changes as per cover sheet

Plans Reference:P1 Date Received:12/04/2024

No.

Date

l		Notes
	•	Builder to verify all dimensions and
		levels on site prior to commencement of
	•	All work to be carried out in accordance

with the current National Construction Code. All materials to be installed according to

manufacturers specifications. · Do not scale from these drawings.

 No changes permitted without consultation with designer.

Designer: ANOTHER PERSPECTIVE PTY LTD PO BOX 21 NEW TOWN

Client / Project info

PROPOSED RESIDENCE

Lot 30, Spoonbill Loop,

SORELL

LIC. NO. 685230609 (S. Turvey) Ph: (03) 6231 4122 Fx: (03) 6231 4166 info@anotherperspective.com.au **R**complete

ELECTRICA	AL PLAN
ST	WH713965

18 March 2024 1:100

Sheet



Lighting



Class 1 & 10a buildings



Building name/description
WH713966 - PROPOSED RESIDENCE, Lot 62, 31 Sunningdale Close, MIDWAY POINT Number of rows preferred in table below (as currently displayed) 2. ENTER CLASSIFICATION

Separate aggregate allowances are calculated for Class 1 cases; for a verandah or balcony; or for a Class 10 building. The % of allowance used' outcomes refer to these aggregate allowances.

							Adjustme	nt factor		CAL	CULATED OU	TCOMES
	Description	Type of space	Floor area of the space	Design lamp or illumination power load	Location	Adjustment factor	Dimming % area	Dimming % of full	Design lumen depreciation	Lamp or illum den		System share of % of aggregate
ID						Adjustment factors	% alea	power	factor	System allowance	System design	allowance used
1	PANTRY	Other	1.0 m ²									
2	LIVING	Living room	18.9 m²									
3	KITCHEN	Kitchen	9.4 m²									
4	BED 2	Bedroom	10.1 m ²									
- 5	BATH	Bathroom	7.5 m²									
6	ENSUITE	Bathroom	4.4 m ²									
. 7	BED 1	Bedroom	11.7 m²									
8	BED 3	Bedroom	9.4 m²			juin i						
9	WIR	Other	2.6 m²]
10	DINING	Lounge room	11.5 m²									
11	WIR 2	Other	2.9 m ²									
12	HALL	Corridor	7.3 m²									
13	L'DRY	Laundry	1.3 m ²								<u> </u>	
14	ENTRY	Corridor	2.4 m²									
15	GARAGE	Other	36.0 m ²									
16	ALFRESCO	Verandah or balcony	13.4 m ²									

149 7 m²

#VALUE! #VALUE! #VALUE!

#VALUE!

IMPORTANT NOTICE AND DISCLAIMER IN RESPECT OF THIS LIGHTING CALCULATOR

Int. Amendment changes as per cover sheet

By accessing or using this calculator, you agree to the following: While care has been taken in the preparation of this calculator, it may not be complete or up-to-date. You can ensure that you are using a complete and up-to-date version by checking the Australian Building Codes Board, the Commonwealth of Australia and States and Territories of Australia do not accept any loss (howsoever caused), damage, injury, expense or cost incurred by any person as a result of accessing, using or relying upons, injury, expense or cost incurred by any person as a result of accessing, using or relying upon this publication, to the maximum extent permitted by law. No representation or warranty is made or given as to the currency, accuracy, reliability, merchantability, fitness for any purpose or completeness of this publication or any information which may appear on any linked websites, or in other linked information surrences and accuracy of the information in relation to their particular circumstances.



© Commonwealth of Australia and the States and Territories of Australia 2023, published by the Australian Building Codes Board.

The material in this publication is licensed under a Creative Commons Attribution—4.0 International licence, with the exception of third party materials and any trade marks. It is provided for general information only and without warranties of any kind. More information on this CC BY licence is



velopment Application: Development Application -Lot 30 Spoonbill Loop, Sorell - P1.pdf

Plans Reference:P1 ate Received:12/04/2024

Date

No.

Notes Builder to verify all dimensions and levels on site prior to commencement of

- of work All work to be carried out in accordance with the current National Construction Code.
- All materials to be installed according to manufacturers specifications.
- Do not scale from these drawings.
- · No changes permitted without consultation with designer.

,	Designer:	Client / Project info
(ANOTHER PERSPECTIVE PTY LTD PO BOX 21 NEW TOWN LIC. NO. 685230609 (S. Turvey)	PROPOSED RESIDENCE Lot 30, Spoonbill Loop, SORELL
	Ph: (03) 6231 4122 Fx: (03) 6231 4166 Email: info@anotherperspective.com.au	



WINDOW MANUFACTURER: (??????WINDOW TYPE CHANGE????)

SW = Sliding Window, AW = Awning Window, SD = Sliding door, FD = French Door, BRPG = Bushfire Rated Privacy Glass NOTE: Window tags including (DG) are to be Double Glazed, otherwise they are to

be single glazed.

Windows supplied MUST HAVE Uw better and or equal to stated figures and SHGC within +/- 5% of stated

Windows labelled YES in "Restricted/protected" column to comply with N.C.C. 11.3.7 & 11.3.8 - Glass specification changed to comply with Bushfire requirements (Refer to Sheet ---)

WINDOW NUMBER	SIZE / TYPE	ID	Uw	SHGC	RESTRICTED
W01	12-16SW (DG)				
W02 12-16SW Opaque (DG)					
W03	09-06AW (DG) Opaque				
W04	18-16AW (DG)				
W05 18-06AW (DG)					
W06 09-27SW (DG)					
W07	18-09SW (DG)				
W08	24-32SD (DG)				
W09 18-24SW (DG)					

INSULATION SCHEDULE			
Area	Insulation Details		
Roof Sarking (vapour permeable) OR R1.3 Anticon Sarking			
Ceiling	R?? bulk insulation (or equivalent) excluding GARAGE		
Walls (external)	R?? bulk insulation (or equivalent) with 1 layer sisalation (vapour permeable). Sisalation only to GARAGE		
Walls (Internal)	N/A or R?? bulk insulation (or equivalent) to internal walls adjacent to GARAGE / SUBFLOOR / ROOFSPACE		
Floors	R?? bulk insulation (or equivalent) to all timber floors		

Clearance is required for uncompressed installation of bulk insulation and timbers should be sized accordingly.

Bulk insulation thicknesses vary depending on manufacturer and should be selected accordingly, and installed to manufacturer's specification.


Min. 20mm clearance required between roofing and vapour permeable sarking (i.e. batten over sarking OR sarking over batten + vented batten)

Min. 25mm air gap above bulk insulation into roof space.
Where solar tubes are located, diffusers are to be installed.

Where skylights are located, ceiling insulation is to be installed to length of shaft.

CALCULATIONS & SCHEDULES

WH713965 ST Sheet 18 March 2024



GUTTER OVERFLOW
REQUIREMENTS as per
N.C.C. Figure 7.4.6a:
Minimum slot opening area of 1200
mm² per metre of gutter and the lower
edge of the slots installed a minimum
of 25 mm below the top of the fascia.
The acceptable overflow capacity
must be 0.5 L/s/m.

Batten fixings: 100mm type 17, 14g bugle screws to comply with AS1684, or refer to AS1684 for alternatives.

> Batten spacing: 75 x 38 F8 @ 900 Centre

Colorbond fixings: 50mm M6 11 x 50 EPDM seal to comply with AS3566 or refer to AS3566 for alternatives.

Roof Sheet Area (Approx)	Fascia Length (Approx)
215.82 m ²	65.6 m

Position and quantity of downpipes are not to be altered without consultation with designer

No.

Date

Area's shown are surface areas / catchment areas, not plan areas.

DOWNPIPE AND ROOF CATCHMENT AREA CALCULATIONS (as per AS/NZS 3500.3)			
Ah¹	198.66	Area of Roof (excluding 115mm Quad gutter) (m²)	
Ah²	206.26	Area of Roof (including 115mm Quad gutter) (m²)	
Ac	249.57	Ah² x Slope factor (Table 3.2 from AS/NZS 3500.3) (m²)	
Ae	6555	Cross sectional area of assumed 57 x 115 Quad Gutter. (mm²)	
DRI	86.90	Design Rainfall Intensity (determined from Appendix D from AS/NZS 3500.3)	
ACDP	74	Catchment area per Downpipe (determined from Figure 3.5.4(A) from AS/NZS 3500.3) (m²)	
Required Downpipes 3.37 Ac ÷ Acdp		Ac ÷ Acdp	
Downpipes Provided	4		

ĒΫ

EAVES VENT NOTE: BRADFORD POLY EAVE VENT TO BE INSTALLED EVERY 3m CONTINUOUS 5mm GAP TO RIDGE

		Sorell Council		
		Development Application: Development Application -Lot 30 Spoonbill Loop, Sorell - P1.pdf		
		Plans Reference:P1 Date Received:12/04/2024		
	Int.	Amendment changes as per cover sheet		

	Notes
•	Builder to verify all dimensions and
	levels on site prior to commencement of

levels on site prior to commencement of work

All work to be carried out in accordance with the current National Construction Code.

Designer:

 All materials to be installed according to manufacturers specifications.

Do not scale from these drawings.
 No changes permitted without consultation with designer.

ANOTHER PERSPECTIVE PTY LTD PO BOX 21	PROPOSED RESIDENCE
NEW TOWN LIC. NO. 685230609 (S. Turvey)	Lot 30, Spoonbill Loop, SORELL
Ph: (03) 6231 4122 Fx: (03) 6231 4166	
Email: ´	
info@anotherperspective.com.au	

Client / Project info

<u> </u>	L
complete	
BY WILSON HOMES	L

ROOF PLAN		
Drawn	ST	WH713965
Date	10 April 2024	Sheet
Scale	1:100	11/03
		11/03